



Product	Name	Speaker Cable			Electrical Characteristics (20°C)	Max. Conductor DC Resistance at 20°C (Ω/M) 0.037
Conductor	Material	Bare Copper				
	Nom.O.D. (mm)	2x37/0.11 (2x0.50mm <sup>2</sup> )	Up	+0.02		
Jacket	External O.D.	2.2 x 4.4 mm	Down	-0.02	Sheath Physical Properties	Rated Temperature(°C) 70°C
			Up	+0.05		
	Surface	Smooth		View		
	Material	PVC(complies RoHS Reach) CPR(Eca)		Drawn By		
				Page		

no.	Packaging	Length (m)	color
15089	Cable coil	10	red/black
15090	Cable coil	25	red/black
15091	Cable coil	50	red/black
15086	Cable Reel	100	red/black
15118	Cable coil	10	transparent
15119	Cable coil	25	transparent
15120	Cable coil	50	transparent
15121	Cable Reel	100	transparent
15109	Cable coil	10	white
15110	Cable coil	25	white
15102	Cable coil	50	white
15101	Cable Reel	100	white

Inner conductor material OFC CU (oxygen-free copper)  
Eca Fire class (CPR) according to DIN EN 13501-6

Änderungen		Datum	Name
Datum	Name	gez.:	26.10.2021 TL
26.10.2021	TL	gepr.:	
		Norm:	
Änderungen vorbehalten / Subject to change			

Bezeichnung	Blatt
LSK 2x0,5mm <sup>2</sup>	1/1
Zeichnungs-Nr.: 15101 15121 15086 15102 15120 15091 15110 15119 15090 15109 15118 15089	von

