



PIN WIRING

P1	P2
1 RED(5V)	4 (VCC)
2 ORANGE	1 (TXD)
3 YELLOW	2 (RXD)
4 GREEN	(RTS#)
5 BLACK	3 (GND)
6 BROWN	(CTS#)

- 模具编号：P-38
- NOTES:
1. ELECTRICAL TEST: 100% OPEN, SHORT & MIS WIRE TEST.
  2. CONTACT RESISTANCE: 0.5ohm,
  3. INSULATOR RESISTANCE: 5M ohm.
  4. HIGH VOLTAGE: DC 300V 0.01sec.
  5. MUST BE ROHS COMPLIANT.

NO.	PART NO	ITEM	DESCRIPTION	QTY	UNIT
①	A.009X01.0400R	CABLE	UL2464 28AWG(7/0.12BC)*4C PVC JACKET COLOR:BLACK OD=3.5±0.1mm L=1780MM	1	PCS
②	B.01004M.0N05R	CONNECTOR	TTL-RS232-PCB(5V) USB A/M CONNECTOR PLASTIC:WHITE	1	PCS
③	J.000008.0500R	TIN WIRE	TIN WIRE OD:0.8MM	3.5	G
④	C.000000.0000R	MOLDING	PE	2.5	G
⑤	C.045P01.0100R	MOLDING	PVC 45P BLACK	12.5	G
⑥	I.000001.0400R	TIE	TIE BLACK L=70MM	1	PCS
⑦	F.0501B0.0100R	TUBE	φ5.5*20mm HEAT TUBE COLOR BLACK	1	PCS
⑧	I.150200.0305R	PE BAG	200*150*0.04MM PE BAG PRINTED BLACK"USB TO RS232 5V AUDIO PLUG 3.5MM"	1	PCS
⑨	B.04035M.0N04R	CONNECTOR	AUDIO PLUG 3.5MM*6.0 4-POLE SHELL NICKEL PLATING PLASTIC: BLACK	1	PCS

Title: Cable USB TTL male >	
3.5 mm 4 pin stereo jack male 5 V	
Date	2015 / 09 / 09
Unit	mm
Projection	
Rev	A
Item no.	83778
Barcode	4043619837786
File No.	88203