



模具编号：P-38

- NOTES:
1. ELECTRICAL TEST: 100% OPEN, SHORT & MIS WIRE TEST.
 2. CONTACT RESISTANCE: 0.5ohm,
 3. INSULATOR RESISTANCE: 5M ohm.
 4. HIGH VOLTAGE: DC 300V 0.01sec.
 5. MUST BE ROHS COMPLIANT.

NO.	PART NO	ITEM	DESCRIPTION	QTY	UNIT
①	A. 009X01. 0400R	CABLE	UL2464 28AWG(7/0.12BC)*4C PVC JACKET COLOR: BLACK OD=3.5±0.1mm L=1780MM	1	PCS
②	B. 01004M 0N06R	CONNECTOR	TTL-RS232-PCB(3.3V) USB A/M CONNECTOR PLASTIC: BLACK	1	PCS
③	J. 000008. 0500R	TIN WIRE	TIN WIRE OD: 0.8MM	3.5	G
④	C. 000000. 0000R	MOLDING	PE	2.5	G
⑤	C. 045P01. 0100R	MOLDING	PVC 45P BLACK	12.5	G
⑥	L. 000001. 0400R	TIE	TIE BLACK L=70MM	1	PCS
⑦	F. 0501B0. 0100R	TUBE	φ5.5*20mm HEAT TUBE COLOR BLACK	1	PCS
⑧	I. 150200. 0306R	PE BAG	200*150*0.04MM PE BAG PRINTED BLACK"USB TO RS232 3.3V AUDIO PLUG 3.5MM"	1	PCS
⑨	B. 04035M 0N04R	CONNECTOR	AUDIO PLUG 3.5MM*6.0 4-POLE SHELL NICKEL PLATING PLASTIC: BLACK	1	PCS



PIN WIRING

P1	P2
1 RED(3.3V)	4 (VCC)
2 ORANGE	1 (TXD)
3 YELLOW	2 (RXD)
4 GREEN	(RTS#)
5 BLACK	3 (GND)
6 BROWN	(CTS#)



Title: Cable USB TTL male >
3.5 mm 4 pin stereo jack male 3.3 V

Item no. **83779**

Barcode 4043619837793

File No. 88203

Date 2015 / 09 / 09

Unit mm

Projection A

Rev