

Delock Converter USB 2.0 male > Serial-TTL 6 open wires 1.8 m (3.3 V)

Description

This USB 2.0 Serial-TTL converter by Delock is due to its wide temperature range most suitable for industrial applications. It supports virtual COM ports and enables optional a direct access to the interface. The converter is multifunctional compatible to the standard systems Windows, Linux and MAC. It is suitable for Embedded systems, control systems, Field Programmable Gate Array, MCUs, dongles etc.



Specification

- Connector: USB 2.0 type A male > Serial-TTL 6 open wires
- Chipset: FTDI 232RL
- Cable gauge: AWG 24
- Temperature range: -20°C to +80°C
- Converter: 5 V / 15 mA (VCC, GND)
- Compatible to UHCI / OHCI / EHCI controller
- LVTTTL 3,3V (data) / 4 mA or HighLevel 12 mA
- No-load current: 70 uA
- Data rate 300 baud - 3 Megabaud
- Databit: 7 or 8
- Stopbits: 1 or 2
- Parity: none, space character, straight, unequal, mark
- Flow control: software XON/XOFF or hardware RTS/CTS
- FIFO: 128 Byte – RX
256 Byte – TX
- Cable length: ca. 1.80 m

System requirements

- Windows XP/XP-64/Vista/Vista-64/7/7-64/8/8-64, Windows CE 4.2, 5.0, 6.0, Mac OS 10.5, 10.6, Linux Kernel 2.6
- PC or laptop with a free USB type A port

Package content

- Converter USB 2.0 > Serial-TTL
- Driver CD
- User manual

Item No. 83117

EAN: 4043619831173

Country of origin: China

Package: Retail Box



Images

