



PIN WIRING

P1	1	RED (5V)	P2	3	(VCC)
	2	ORANGE		4	(TXD)
	3	YELLOW		5	(RXD)
	4	GREEN		6	(RTS#)
	5	BLACK		1	(GND)
	6	BROWN		2	(CTS#)

- 模具编号：P-38
- NOTES:
1. ELECTRICAL TEST: 100% OPEN, SHORT & HIS WIRE TEST.
 2. CONTACT RESISTANCE: 0.5ohm.
 3. INSULATOR RESISTANCE: 5M ohm.
 4. HIGH VOLTAGE: DC 300V 0.01sec.
 5. MUST BE ROHS COMPLIANT.

NO.	PART NO	ITEM	DESCRIPTION	QTY	UNIT
⑩	I.180150.0301R	PE BAG	180*150*0.04MM PE袋 PRINTED BLACK FONT	1	PCS
⑨	F.0501B0.0100R	TUBE	USB Cable w/FTDI set to 5V"	1	PCS
⑧	I.000001.0400R	TIE	TIE BLACK L=70MM	1	PCS
⑦	E.00254M.0100R	HOUSING	Dupont 2.54mm 1*1P HOUSING	6	PCS
⑥	D.00254F.1400R	TERMINAL	Dupont 2.54mm TERMINAL	6	PCS
⑤	C.045P01.0100R	MOLDING	PVC 45P BLACK	5.5	G
④	C.000000.0000R	MOLDING	PE	2.5	G
③	J.000008.0500R	TIN WIRE	TIN WIRE OD:0.8MM	3.5	G
②	B.01004M.0N05R	CONNECTOR	TTL-RS232-PCB(5V) USB A/M CONNECTOR PLASTIC: WHITE	1	PCS
①	A.009X01.0603R	CABLE	UL2464 26AWG(7/0.16TC)*6C(RED,ORANGE, GREEN, BLACK, YELLOW, BROWN)+AL FOIL PVC JACKET COLOR: BLACK OD=5.0±0.1mm L=1830MM	1	PCS



Title: Cable USB male > TTL 6 pin pin header female separate 5 V

Item no. **83786**

Barcode 4043619837861

File No. 88203

Date	2015 / 09 / 10
Unit	mm
Projection	
Rev	A